


FIS Aerial Judges Stand Requirements


Revision 10/10/2002 • FIS Freestyle Committee




Location on course

Explanatory Notes:


1. Permanent, fully enclosed buildings are preferred.
2. **Minimum size** of stand interior to be 12.5m x 3m for FIS World Cup. Requirements for FIS World Championships and Olympic Games will call for the stand to be larger. (e.g. TV, video, computer, scoreboard, sound)
3. The stand is positioned so that:
 - Judges 1 to 5 are able see take off and landing,
 - Judges 6 & 7 are able see landing and exit,
 - Announcer is able see start, landing and exit.
4. Entrance should be by staircase in the middle back of the stand, and have a door to restrict access during competition. Alternately, an internal staircase with entrance at the uphill back of stand can be used. **Entry can never be from the front of the stand or through computer section.**
5. The entire judges stand should be adequately heated. Temperature to be 15°C - 24°C in Computer section.
6. Computer/Announcer section **must be dry, heated and totally enclosed** against wind, snow and rain.
7. The stand is to have a sloping, waterproof roof. Cantilever roof in judges' section as per detail below.
8. Judges divisions should be constructed as per detail on page 4.
9. Uninterruptable (UPS) Clean 110 volt or 220 volt mains double power points to 7 positions as marked on plan - X
10. The floor of the stand should be dry, slip resistant and free of obstacles and holes.
11. It must be possible for the judges to have visual contact with the announcer and scorer.
12. Portable toilet must be located close to judges stand.
13. Judges stand to be located next to Jump 1.
14. **IMPORTANT:** If other users require space on the stand (i.e. TV, video, sound), sizes need to be increased to accomodate them, however the location and space reserved for FIS users should not to be compromised.



Plan view



Elevation



Side (section) views